SITE DEVELOPMENT APPLICATION



360 Main St. ● Delta, Colorado 81416 ● Phone (970) 874-7903 ● Fax (970) 874-6931 ● website: <u>www.delta-co.gov</u>

The six sets of plans submitted with your application for Site Development should have details **specific to the exterior of the proposed building** as outlined in the *Site Development Plan Checklist*. These complete, bound sets of plans should include the site plan (e.g. building footprint, parking, etc.), one elevation drawing for review of architectural compliance, a landscape plan, an irrigation plan, a utility plan and a drainage-grading plan.

The review of these plans will likely be completed within 10 working days from when <u>all</u> required information has been submitted. Incomplete sets will NOT be processed.

- □ The two sets of building plans, with all information necessary to construct a building in compliance with our adopted codes, *may** be submitted with a building-permit application and a plan-review fee at the same time you submit your Site Development application.
 - * Because we require the plan-review fee to be paid at the time you submit *building* plans, you may wish to apply for a building permit after you know that your proposed site-development is (or will be) approved. Otherwise, should your building-design change due to site-development requirements, you would be required to pay another plan-review fee for our review of the new building design.

The review of the building plans will likely be completed within 10 working days.

The stated estimate of review time for either submittal is based on your documents being complete, accurate and of professional quality; anything less will slow the process.

Please find attached:

- Application for Site Development (pages 2 & 3).
- Site Development Plan checklist (pages 4-6).
- Site Development Standards (pages 7-11).
- Minimum parking-lot dimensions and configurations (pages 12-17).
- * Copy of Site Development Ordinance available upon request.
- * Building Permit Application available upon request.



APPLICATION FOR SITE DEVELOPMENT

Date Received:				
Contact Person (Name only one please	:)	Phone	Fax	e-mail
Street Address of Site Development				
Name of Applicant/Owner (include recorde	ed copy of deed/tit	le insurance poli	cy showing legal des	scription and ownership)
Mailing Address of Applicant/Owner				Day Phone
Class of Work: New Addition Demolish Zoning District: Residential Commercial Industrial Use of new building or addition	Remodel Repair Move			

Lot	Landscape Requirement
(A)	Total square footage of Lot (L x W)
(B)	Total square footage of building(s)
(C)	Square footage for landscape determination (A minus B)
(D)	Required lot landscaping (square feet) Multiply (C) by either
	4% (.04) for industrial zoning district 8% (.08) for commercial zoning district 15% (.15) for residential zoning district
Froi	ntage Landscape Requirement
(E)	Total Lot right-of-way frontage
(F)	Multiply (E) by 25% (.25) for each street frontageOR
	Multiply (E) by 70% (.70) for State Highway or Crawford Ave. frontage
(G)	Multiply (F) by 15 feet to determine square footage of landscape required
Park	ing Spaces: Provided
	Required
(G	OTE: The larger of (D) or (G) represents the <u>minimum</u> landscape required on the lot;) represents that portion of the required landscape that must be placed upon lot frontage. Iditional parking lot landscaping may be required.
	Proposed lot landscape (square feet)
-	Proposed frontage landscape (linear feet)
•	Proposed frontage landscape (square feet)
	reby acknowledge that I have read this application and state that the above is correct and e to comply with the City ordinances and City standards regulating site development.
Sign	nature of Applicant/OwnerDate
This a	application must be submitted with the Site Development Plan; please refer to the attached Site Development Plan clist for details. The Plan must be an accurate to-scale drawing large enough to show the required details, but not less than

Application for Site Development Cont.

1"/40'. Please allow at least two weeks for Plan review. Incomplete submittal may be rejected and can cause delays. (Updated 11-04)



Site Development Plan Checklist

Project Name:			
Pr	Project Address:		
	te: This checklist is a guide only. Applicants are responsibulations.	le for fulfilling all applicable local, state, and federal	
	Three (3) copies (if applicable) of plans, including: Site Plan Drainage & grading plans Landscaping Plan Irrigation plan Lighting plan Utility plans Sign Plans Curb, Gutter & Sidewalk Plans Storm-water Management Plan Mechanical Equipment/Trash Screening	□ Site Plan General Elements: □ Scale (define) not less than 1" = 40' □ North arrow, date prepared □ Name of company, contact person(s) □ Property lines □ Existing and proposed structures □ Curb, gutter, and sidewalk; pedestrian walkways on-site □ Parking: location of existing and proposed off-street parking areas, driveways and parking islands □ Location of abutting public rights-of-way □ Curb radii (horizontal control plan) □ Dimensions must include lot size, building size, length and width of each landscaped areaThe location of all existing and proposed signage □ 2-foot contour lines □ Existing & proposed utilities & site drainage	
	One (1) copy of other applicable documents including: Deed or title insurance policy evidencing ownership and legal description of site SID Covenant for curb, gutter, sidewalk, paving if applicable Landscape Maintenance Covenant Declaration of Covenants CDOT access permit Necessary State or Federal permits	□ Highway Corridor Overlay District? ○ Stricter standards apply. □ Zoning Issues ○ Zone ○ Setbacks □ Front □ Sides □ Rear □ Corner ○ Height □ Zoning district height:	
	Storm water & Drainage Plan: Drainage, grading prepared by licensed, professional engineer as required by site development standards 100-year/24-hour storm event run-off calculations, peak discharge(s) Existing and proposed site drainage 2-foot contour lines (or smaller, if applicable) swales/ditches, with details on ground cover, slope	□ Lighting Plan □ The location and types of all existing and proposed outdoor and exterior lighting and fixtures including illuminated signs. □ Where requested by the City, the plan shall also include a mounting height, mounting method, location, type, lumen output, manufacturer's catalog cuts, photometric report with candela distribution,	

□ Landscape Plan: □ Landscape draes, vegetation type, tree caliper widths & height at planting, bush sizes □ Include calculations which establish compliance with landscape overage requirements. □ Location of all non-plant materials, with details on type, size, and depth (e.g. rock, wood chips) □ A minimum of 1 tree and 3 bushes for every 800 sq. ft. of landscaped area □ 80% of landscaped areas must be living plant material at maturity, unless otherwise authorized □ Landscaped parking lots for all lots with more than 15 spaces "See next page □ Landscaped parking lots for all lots with more than 15 spaces "See next page □ Landscaped parking lot islands ○ required for all sites with more than one driving aisle or more than 25 spaces ○ each island must provide at least one tree, and is subject to the 80% ground coverage requirement □ Landscape coverage (excluding buildings) ○ 15% residential zones ○ 8% business zones ○ 4% industrial zones □ Frontage Landscaping ○ 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) □ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) □ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. ○ Proposed sewer and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Collector of the collection of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii □ Adequate turn-around for dead-end parking areas	_	T 1 D1	T 1 TN / // I
height at planting, bush sizes Include calculations which establish compliance with landscape coverage requirements. Cocation of all non-plant materials, with details on type, size, and depth (e.g. rock, wood chips) Smiths 5 gallon min. size no thomy shrubs or trees near sidewalks or recreation areas some stop in the first of landscaped area must be living plant material at maturity, unless otherwise authorized Landscaped parking lots for all lots with more than 15 spaces *See next page Landscaped parking lot islands required for all sites with more than one driving aisle or more than 25 spaces each island must provide at least one tree, and is subject to the 80% ground coverage requirement Landscape coverage (excluding driveways and sidewalks (1 tree every 30' of frontage) 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Specifications Corridor Overlay: Toposed access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas Maintain turning radii Maintain			<u>*</u>
□ Include calculations which establish compliance with landscape coverage requirements. □ Location of all non-plant materials, with details on type, size, and depth (e.g. rock, wood chips) □ A minimum of I trea and 3 bushes for every 800 sq. ft. of landscaped area ■ 80% of landscaped area must be living plant material at maturity, unless otherwise authorized □ Landscaped parking lots for all lots with more than 15 spaces *See next page □ Landscaped parking lot islands □ required for all sites with more than one driving aisle or more than 25 spaces □ each island must provide at least one tree, and is subject to the 80% ground coverage requirement □ Landscape coverage (excluding buildings) □ 15% residential zones □ Frontage Landscaping □ 15 deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) □ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30° of frontage) □ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30° of frontage) □ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. □ Proposed sewer and water tap sizes, proposed locations □ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) ■ Adequate turn-around for dead-end parking areas □ Driveway With adequate? Minimum turning radii			
landscape coverage requirements. Location of all non-plant materials, with details on type, size, and depth (e.g. rock, wood chips) A minimum of 1 tree and 3 bushes for every 800 sq. ft. of landscaped area must be living plant material at maturity, unless otherwise authorized Landscaped parking lots for all lots with more than 15 spaces *See next page Landscaped parking lots for all lots with more than 16 susheer to the 80% ground coverage requirement Landscaped parking lot islands required for all sites with more than one driving aisle or more than 25 spaces each island must provide at least one tree, and is subject to the 80% ground coverage requirement Landscape coverage (excluding buildings) 15% residential zones Frontage Landscaping Fortage Landscaping 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas			
Landscape coverage requirements. stress of all non-plant materials, with details on type, size, and depth (e.g. rock, wood chips) on thomy shrubs or trees near sidewalks or recreation areas not homy shrubs or trees near sidewalks or recreation areas not homy shrubs or trees near sidewalks or recreation areas not homy shrubs or trees near sidewalks or recreation areas not homy shrubs or trees near sidewalks or recreation areas naturity, unless otherwise authorized		Include calculations which establish compliance with	
□ Location of all non-plant materials, with details on type, size, and depth (e.g. rock, wood chips) □ A minimum of 1 tree and 3 bushes for every 800 sq. ft. of landscaped area ■ 80% of landscaped area must be living plant material at maturity, unless otherwise authorized □ Landscaped parking lots for all lots with more than 15 spaces "See next page □ Landscaped parking lot islands ○ required for all sites with more than one driving aisle or more than 25 spaces ○ each island must provide at least one tree, and is subject to the 80% ground coverage requirement □ Landscaped coverage (excluding buildings) ○ 15% residential zones ○ 15% residential zones ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ 15° deep on 25% of all frontages, excluding driveways			
size, and depth (e.g. rock, wood chips) A minimum of I tree and 3 bushes for every 800 sq. ft. of landscaped area 80% of landscaped areas must be living plant material at maturity, unless otherwise authorized Landscaped parking lots for all lots with more than 15 spaces *See next page Landscaped parking lot islands required for all sites with more than one driving aisle or more than 25 spaces each island must provide at least one tree, and is subject to the 80% ground coverage requirement Landscape coverage (excluding buildings) 15% residential zones Frontage Landscaping 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Lutility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Landscaped areas must be living plant material at maturity, unless otherwise authorized under the maturity and cottonwoods (Aspen & Narrowleaf Cottonwood excepted) on tores usacelible to Dutch Elm dia Cottonwood excepted) on tores usacelible to Dutch Elm dia Cottonwood excepted) on tores usacelible weed barrier maximum 20% inert materials cock: 1"—3" size, 3" minimum depth Sight Corner Specifications Minor arterial and arterial streets: no plants over 42" for 60' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Newly installed landscape parcels in excess of eight hundred (800) square feet shall include a properly designed and functioning automatic irrigation system providing full coverage to all plant material. plants from the firm of			
□ A minimum of 1 tree and 3 bushes for every 800 sq. ft. of landscaped area must be living plant material at maturity, unless otherwise authorized □ Landscaped parking lot so for all lots with more than 15 spaces "See next page □ Landscaped parking lot islands ○ required for all sites with more than one driving aisle or more than 25 spaces ○ each island must provide at least one tree, and is subject to the 80% ground coverage requirement □ Landscape coverage (excluding buildings) ○ 15% residential zones ○ 8% business zones ○ 4% industrial zones ○ 8% business zones ○ 4% industrial zones ○ 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. ○ Proposed sever and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas □ Driveway Wildth adequate? Minimum turning radii Alequate turn-around for dead-end parking areas □ Driveway Wildth adequate? Minimum turning radii	-		
of landscaped area 80% of landscaped areas must be living plant material at maturity, unless otherwise authorized Landscaped parking lots for all lots with more than 15 spaces *See next page Landscaped parking lot islands required for all sites with more than one driving aisle or more than 25 spaces each island must provide at least one tree, and is subject to the 80% ground coverage requirement Landscape coverage (excluding buildings) 15% residential zones Frontage Landscaping 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning readii			
Bo% of landscaped areas must be living plant material at maturity, unless otherwise authorized Landscaped parking lots for all lots with more than 15 spaces *See next page Landscaped parking lot islands orequired for all sites with more than one driving aisle or more than 25 spaces oeach island must provide at least one tree, and is subject to the 80% ground coverage requirement Landscape coverage (excluding buildings) o 15% residential zones o 4% industrial zones o 4% industrial zones of frontage of front		· · · · · · · · · · · · · · · · · · ·	
maturity, unless otherwise authorized Landscaped parking lots for all lots with more than 15 spaces "See next page Landscaped parking lot islands orequired for all sites with more than one driving aisle or more than 25 spaces each island must provide at least one tree, and is subject to the 80% ground coverage requirement Landscape coverage (excluding buildings) 15% residential zones 4% industrial zones Frontage Landscapin 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Praffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Mainimum 12% innert materials cock: 1"—3" size, 3" minimum depth wood chips: 3" minimum depth wood chips: 3" minimum depth Sight Corner Specifications Minor arterial and arterial streets: no plants over 42" for 60' from street corner Collector streets: no plants over 42" for 35' from street corner Collector streets: no plants over 42" for 35' from street corner Newly installed landscape parcels in excess of eight hundred (800) square feet shall include a properly designed and functioning automatic irrigation system providing full coverage to all plant material. plants from the provided and functioning automatic irrigation system providing full coverage to all plant material. plants from the provided access on private or public property (e.g. Easements, City and/or CD			
□ Landscaped parking lots for all lots with more than 15 spaces *See next page □ Landscaped parking lot islands ○ required for all sites with more than one driving aisle or more than 25 spaces ○ each island must provide at least one tree, and is subject to the 80% ground coverage requirement □ Landscape coverage (excluding buildings) ○ 15% residential zones ○ 8% business zones ○ 4% industrial zones □ Frontage Landscaping ○ 15° deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30° of frontage) ○ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. ○ Proposed sewer and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas □ Driveway Width adequate? ■ Minimum 20% inert materials □ wood chips: 3° minimum depth □ Winimum 20% inprint and exterial and arterial streets: no plants over 42° for 50° from street corner □ Local streets: no plants over 42° for 50° from street corner □ Local streets: no plants over 42° for 50° from street corner □ Newly installed landscape parcels in excess of eight hundred (800) square feet shall include a properly designed and functioning automatic irrigation □ system providing full coverage to		80% of landscaped areas must be living plant material at	
spaces *See next page Landscaped parking lot islands orequired for all sites with more than one driving aisle or more than 25 spaces oeach island must provide at least one tree, and is subject to the 80% ground coverage requirement Landscape coverage (excluding buildings) o 15% residential zones o 8% business zones o 4% industrial zones Frontage Landscaping of 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) o Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of finghway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. O Proposed sewer and water tap sizes, proposed locations O Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii			☐ geotextile weed barrier
spaces *See next page Landscaped parking lot islands o required for all sites with more than one driving aisle or more than 25 spaces o each island must provide at least one tree, and is subject to the 80% ground coverage requirement Landscape coverage (excluding buildings) o 15% residential zones o 8% business zones o 4% industrial zones o 15% deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc, service. O Proposed sewer and water tap sizes, proposed locations O Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffie/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii			□ maximum 20% inert materials
□ Landscaped parking lot islands ○ required for all sites with more than one driving aisle or more than 25 spaces ○ each island must provide at least one tree, and is subject to the 80% ground coverage requirement □ Landscape coverage (excluding buildings) ○ 15% residential zones ○ 8% business zones ○ 4% industrial zones □ Frontage Landscaping ○ 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Lillity Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. ○ Proposed sewer and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) □ Adequate stacking/storage at entryways & drive-up windows □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimium turning radii			
o required for all sites with more than one driving aisle or more than 25 spaces o each island must provide at least one tree, and is subject to the 80% ground coverage requirement □ Landscape coverage (excluding buildings) o 15% residential zones o 4% industrial zones o 4% industrial zones o 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) o Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) o Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. o Proposed sewer and water tap sizes, proposed locations o Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii Sight Corner Specifications Minor arterial and arterial streets: no plants over 42" for 50' from street corner Collector streets: no plants over 42" for 50' from street corner Collector streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants over 42" for 50' from street corner Local streets: no plants		Landscaped parking lot islands	
aisle or more than 25 spaces			coa empor o minimum depui
o each island must provide at least one tree, and is subject to the 80% ground coverage requirement Landscape coverage (excluding buildings)			Sight Corner Specifications
is subject to the 80% ground coverage requirement Landscape coverage (excluding buildings) 15% residential zones 4% industrial zones Frontage Landscaping 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii 60' from street corner Collector streets: no plants over 42" for 35' from street corner Collector streets: no plants over 42" for 35' from street corner Collector streets: no plants over 42" for 35' from street corner Collector streets: no plants over 42" for 35' from street corner Collector streets: no plants over 42" for 35' from street corner Collector streets: no plants over 42" for 35' from street corner Collector streets: no plants over 42" for 35' from street corner Newly installed landscape parcels in excess of eight hundred (820) square feet shall include a properly designed and functioning automatic irrigation Newly installed landscape parcels in excess of eight hundred (820) square feet shall include a properly designed and functioning automatic irrigation Newly installed landscape parcels in excess of eight hundred (820) square feet shall include a properly designed and functioning automatic irrigation Newly installed landscape parcels in excess of eight hundred (820) square feet shall include a properly designed and functioning automatic irrigation Newly instal			
requirement Landscape coverage (excluding buildings)			
□ Landscape coverage (excluding buildings) ○ 15% residential zones ○ 8% business zones ○ 4% industrial zones □ Frontage Landscaping ○ 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. ○ Proposed sewer and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Call streets: no plants over 42" for 35' from street corner			
o 15% residential zones o 8% business zones o 4% industrial zones □ Frontage Landscaping o 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) ○ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. ○ Proposed sewer and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. □ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. ○ Proposed sewer and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information of adequate tap/lateral sizes. □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? ■ Minimum turning radii		•	Collector streets: no plants over 42" for 50' from street
 8% business zones 4% industrial zones Frontage Landscaping 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii 			corner
o 8% business zones o 4% industrial zones Frontage Landscaping o 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) o Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) o Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) o Litility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. o Proposed sewer and water tap sizes, proposed locations o Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii Irrigation Plan: O Newly installed landscape parcels in excess of eight hundred (800) square feet shall include a property designed and functioning automatic irrigation o system providing full coverage to all plant material. O plans shall include pipe materials, width, sprinkler type, pumps, type of irrigation and location of water source, etc. O backflow prevention device is required Special sewer discharge requirements: All commercial and industrial uses must fill out a Pre-Treatment Questionnaire Sampling manhole may be required (see City of Delta Engineering Specifications)			□ Local streets: no plants over 42" for 35' from street
o 4% industrial zones Frontage Landscaping o 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) o Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) o Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) □ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. ○ Proposed sewer and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas □ Driveway Width adequate? ■ Minimum turning radii □ Minimum turning radii □ Minimum turning radii □ Newly installed landscape parcels in excess of eight hundred (800) square feet shall include a property designed and functioning automatic irrigation ○ System providing full coverage to all plant material. ○ plans shall include pipe materials, width, sprinkler type, pumps, type of irrigation and location of water source, etc. ○ backflow prevention device is required □ Special sewer discharge requirements: □ All commercial and industrial uses must fill out a Pre-Treatment Questionnaire □ Sampling manhole may be required (see City of Delta Engineering Specifications) □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii		o 8% business zones	•
 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii 		 4% industrial zones 	
 15' deep on 25% of all frontages, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii 		Frontage Landscaping	☐ Irrigation Plan:
driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) System providing full coverage to all plant material. Coplans shall include pipe materials, width, sprinkler type, pumps, type of irrigation and location of water source, etc. Coplans shall include pipe materials. All commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-Treatment Questionnaire Commercial and industrial uses must fill out a Pre-			
frontage) Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Diameter and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Praffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii			
 Corridor Overlay: 70% of highway frontage, excluding driveways and sidewalks (1 tree every 30' of frontage) Itility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Praffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii Special sewer discharge requirements:			
excluding driveways and sidewalks (1 tree every 30' of frontage) o system providing full coverage to all plant material. o plans shall include pipe materials, width, sprinkler type, pumps, type of irrigation and location of water source, etc. o backflow prevention device is required Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. o Proposed sewer and water tap sizes, proposed locations o Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Special sewer discharge requirements:			
every 30° of frontage) material. plans shall include pipe materials, width, sprinkler type, pumps, type of irrigation and location of water source, etc. backflow prevention device is required "Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. "Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii			<u> </u>
o plans shall include pipe materials, width, sprinkler type, pumps, type of irrigation and location of water source, etc. o backflow prevention device is required □ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. o Proposed sewer and water tap sizes, proposed locations o Please contact the City Engineer to obtain information on adequate tap/lateral sizes. □ All commercial and industrial uses must fill out a Pre-Treatment Questionnaire □ Sampling manhole may be required (see City of Delta Engineering Specifications) □ Traffic/Circulation: □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) □ Adequate stacking/storage at entryways & drive-up windows □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii			
sprinkler type, pumps, type of irrigation and location of water source, etc. backflow prevention device is required Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. Proposed sewer and water tap sizes, proposed locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii		every 30° of frontage)	
Docation of water source, etc. backflow prevention device is required			 plans shall include pipe materials, width,
Docation of water source, etc. backflow prevention device is required			sprinkler type, pumps, type of irrigation and
□ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. ○ Proposed sewer and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. □ All commercial and industrial uses must fill out a Pre-Treatment Questionnaire □ Sampling manhole may be required (see City of Delta Engineering Specifications) □ Traffic/Circulation: □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) □ Adequate stacking/storage at entryways & drive-up windows □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii			
□ Utility Plan: [All existing and proposed sewer, water, electric, gas, cable etc. service. ○ Proposed sewer and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. □ All commercial and industrial uses must fill out a Pre-Treatment Questionnaire □ Sampling manhole may be required (see City of Delta Engineering Specifications) □ Traffic/Circulation: □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) □ Adequate stacking/storage at entryways & drive-up windows □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii			·
electric, gas, cable etc. service. O Proposed sewer and water tap sizes, proposed locations O Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: O Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii			o outliness provention device is required
electric, gas, cable etc. service. O Proposed sewer and water tap sizes, proposed locations O Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: O Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii		Utility Plan: [All existing and proposed sewer water	Special sewer discharge requirements:
 ○ Proposed sewer and water tap sizes, proposed locations ○ Please contact the City Engineer to obtain information on adequate tap/lateral sizes. □ Traffic/Circulation: □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) □ Adequate stacking/storage at entryways & drive-up windows □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii 	_		
locations Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii			
 Please contact the City Engineer to obtain information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii 			
information on adequate tap/lateral sizes. Traffic/Circulation: Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii			
Traffic/Circulation: □ Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) □ Adequate stacking/storage at entryways & drive-up windows □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii			Engineering Specifications)
 Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii 		information on adequate tap/lateral sizes.	
 Documentation of approved access to private or public property (e.g. Easements, City and/or CDOT Access Permit) Adequate stacking/storage at entryways & drive-up windows Adequate turn-around for dead-end parking areas Driveway Width adequate? Minimum turning radii 			
 □ Adequate stacking/storage at entryways & drive-up windows □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii 	Tra		
 □ Adequate turn-around for dead-end parking areas □ Driveway Width adequate? □ Minimum turning radii 			
Driveway Width adequate?Minimum turning radii			WS
☐ Minimum turning radii		Adequate turn-around for dead-end parking areas	
☐ Minimum turning radii		Driveway Width adequate?	
Tracquate maneavering space for trash & derivery service		Adequate maneuvering space for trash & delivery service	

Parking Lots: Parking lot design which meets dimensional requirements in City Standards & Specifications Manual Sufficient parking spaces to meet zoning requirements **Screening Requirements:** Lots with more than 15 spaces –a minimum of 5% Building Elevations, including roof mounted HVAC landscaping integral to parking area units and proposed screening For lots with more than 1 driveway aisle or 25 spaces, Location of trash receptacle areas, loading dock areas, islands covering at least 6% of parking lot area. storage areas. ☐ Each island large enough for a mature tree and These must be screened from adjoining rightsno less than 6' at its longest dimension of-way and residential areas.. Concrete curbing around islands Hard surfaced if more than 6 spaces Bike Rack location (optional, but encouraged) Wheel stop locations (optional, but encouraged) Backing into street is prohibited for off-street parking ADA Requirements (see attached sheet) If in Highway Corridor (if any part of the Highway Corridor (continued) Exterior mechanical equipment either incorporated into property lies within 400' of a State highway form of building or screened from any street view, with or Crawford Avenue right-of-way line), the similar materials to main building following standards apply: Refuse collection areas screened from view from any Architectural Elevation Drawings street with materials similar to landscaping and main **Building Material Details** Photographs/examples of building materials All landscaping areas may have a maximum 20% 24% contrasting material on front, 20% sides and rear coverage of inert materials such as paving stones, lava 70% of highway frontage(s), excluding driveways, shall rock, river rock, pea gravel, etc. be landscaped to a depth of 15 feet Parking areas on the front or side of a building with 25 25% of secondary frontages, excluding driveways, shall or more spaces shall have landscaped islands throughout be landscaped to a depth of 15 feet the parking area, totaling a minimum of 6% of the Architectural elements (dormers, roof overhangs, parking area protective canopies, and creatively shaped window Metal skinned buildings not permitted in B-1 Zone openings, pitched roofs) Other information requested by City Staff to review the application's conformance to City Codes and Regulations

Note: Failure to comply with these requirements may result in denial or delay of issuance of the building permit.

Updated 11-19-04

15.04.080 Site development and maintenance requirements.

- A. No building permit for new construction or additions to existing structures, except for single family residences, duplexes, farms, ranches and accessory buildings thereto, shall be issued until a site development plan has been approved pursuant to this Section. Provided, however, a site development plan is not required for (a) an addition which increases the building footprint by 50% or less, or has construction value of less than \$20,000; or (b) the erection of an accessory building to an existing building which increases the aggregate building footprint by 50% or less, or has a construction value of less than \$20,000.
- B. The site development plan shall be submitted on forms provided by the City with a building permit application and comply with the following requirements:
- 1. Plans and specifications shall be submitted, drawn to a scale adequate to clearly show all required features and not less than 1" equals 40 feet, for the construction of the following improvements consistent with City construction standards, specifications and design standards.
- a. Installation of new, or repair of damaged, curb, gutter and sidewalk along abutting streets, except in subdivisions where it is not required by current subdivision regulations.
- b. Required off-street parking spaces, including landscaped areas, and maneuvering areas, adequate to avoid the necessity of backing onto the developed part of adjoining streets, and adequate to meet all applicable requirements. When six or more spaces are required, the required parking and maneuvering areas shall be paved.
- c. Site drainage adequate to avoid damage or adverse effects to improvements, structures and property on and off the site.
- d. Landscaping, including provisions for trees and shrubs, subject to the following minimum requirements:
- i. At least 25% of the linear frontage of the site abutting public street rights-of-way to a minimum width of fifteen feet, unless the City approves an alternative plan as more effectively presenting a landscaped view from the abutting street rights-of-way; and
- ii. Inclusive of the above frontage requirement, landscaping shall be required in at least 15% of that part of the site not covered by buildings for sites located in residential zoning districts; at least 8% of that part of the

site not covered by buildings for sites located in commercial zoning districts; and at least 4% of that part of the site not covered by buildings for sites located in industrial zoning districts.

- iii. In addition, parking areas with 25 or more spaces or more than one isle, shall incorporate landscaped islands disbursed throughout the parking with areas totaling a minimum of 6% of the parking area.
- iv. Such landscaping shall consist of trees, shrubs, and ground covers, and may include up to a maximum of 20% coverage in inert materials such as decorative paving stones, lava rock, pea gravel, etc., except to the extent such area is lawfully covered by a building.
- v. In addition, property within the defined highway corridor of Section 15.04.090 shall also meet the requirements therein.
 - e. Driveways, culverts and curb cuts.
- f. All outdoor lighting fixtures shall be shielded so that the light source is not directly visible off the premises.
- 2. The current deed to the property or other evidence of title shall be submitted with the plan.
- 3. If the abutting street is not paved, a recordable covenant binding the property for assessments for the cost of paving and related improvements must be properly executed and submitted.
- C. In those cases where the grade for curb, gutter and sidewalk cannot be established by the City or immediate construction is impractical, a recordable covenant binding the property to pay for such improvements or other security pursuant to Subsection 15.20.020(B) may be accepted by the City in lieu of immediate construction of the curb, gutter or sidewalk.
- D. Any improvement, the construction of which has been secured pursuant to City Subdivisions Regulations, Planned Unit Development Regulations or by other contract, need not be provided as part of the site development plan.
- E. Following review, revision and approval by the City, the plan and specifications as approved by the City shall be revised in final form, stamped with City's approval and filed with the City. Thereafter, a building permit may be issued.

- F. No occupancy permit shall be issued until the required improvements are constructed and approved by the City in compliance with the approved plans or secured for completion within 6 months, and a recordable maintenance covenant running with the land on forms provided by the City is executed, approved by the City, and recorded.
- G. All required improvements and landscaping shall be maintained in good repair and safe condition. Violation of this provision is hereby declared to be a nuisance which may be abated by the City in any lawful manner.
- H. 1. Variances by the Planning Commission may be granted from the requirements of Subsection (B) above if it determines following the review procedure of Section 17.04.290 of City Zoning Regulations that all the criteria of this Subsection H are met:
- a. The variance is requested for an addition to an existing building or construction of a purely accessory structure.
- b. The variance will not adversely affect the public health, safety or welfare.
- c. The addition or structure will have a *de minimum* effect on traffic, parking and drainage.
- d. The variance requested is the minimum variance that will afford relief.
- e. The variance will not result in development incompatible with other property or buildings in the area and will not affect or impair the value, use or development of other property.
- f. Strict compliance is technically infeasible or the cost of the required site improvements is substantially more than the cost of the addition or structure, and the addition or structure is insignificant with respect to the structures already on the premises.
- 2. Published or delivered notice of the hearing as specified in Subsection 17.04.290(D) is not required.
- I. Following approval of a site development plan, requests for amendments may be filed with the City and shall be reviewed in accordance with the provisions of Paragraphs (B), (C), (D), (E), and (F) above.

- J. The City Manager is authorized to issue supplemental regulations to implement, interpret and administer these provisions and to provide detailed standards and specifications, consistent herewith.
- K. Where there are practical difficulties or unnecessary hardships in the way of carrying out the strict letter of these requirements, upon written application, the City Council may vary or modify the application of these requirements, so that the spirit of the requirements is observed, public safety and welfare secured, and substantial justice done. (Ord. 6, §1, 2004; Ord. 4, §1 & 2, 2005)

15.04.090 Supplemental site development standards for highway corridors.

- A. Property, any part of which is located within 400 feet of a right-of-way line of Highways 50 and 92, or Crawford Avenue west of Hillcrest Drive, shall be subject to the following Supplemental Site Development Standards in addition to other applicable requirements. Whichever City ordinance or regulation requires the more stringent or restrictive requirement shall apply. Provided, however, a site development plan is not required for (a) an addition which increases the building footprint by 50% or less, or has construction value of less than \$20,000; or (b) the erection of an accessory building to an existing building which increases the aggregate building footprint by 50% or less, or has a construction value of less than \$20,000.
- Building facades which are substantially constructed of smooth-face concrete, smooth-face concrete block, or metal siding, or similar monolithic building materials shall be designed to include either a) two (2) foot eaves and a different colored pitched roof with a height between the top of the roof and the eave of at least equal to the distance from the eave to the ground, or a 8:12 pitch; or b) other surface materials on a minimum of 24% of area of the front, and on 20% on each side and Such materials may include, but are not limited to, contrasting materials such as glass, brick, stucco, wood or stone. In either case, other architectural elements must also be included in the design which include but are not limited to architectural projections such as dormers, roof overhangs, protective canopies, and creatively shaped window openings. Metal skinned buildings are not allowed within the B-1 Zoning District.
- 2. Exterior mechanical equipment, including electrical transformers, shall either be incorporated in the overall form of the building or screened from view from any street by

materials consistent with the landscaping, safety, the main building, and the National Electrical Code.

- 3. Refuse collection containers and areas shall be screened from view from any street or residential area by materials consistent with the landscaping and building.
- 4. a. Landscaping shall be installed and maintained to a minimum depth of 15 feet along 70% of the frontages of the State Highway or Crawford Avenue west of its intersection with Hillcrest Drive, excluding driveways and sidewalks.
- b. Landscaping shall be installed and maintained to a minimum depth of 15 feet along a minimum of 25% of the secondary street frontages, excluding driveways and sidewalks.
- B. The regulations of this Section shall apply to the entire building, lot, parcel or contiguous lots or parcels which constitute a single site, when any part thereof is located within 400 feet of the right-of-way of the highway or street segments described in Subsection (A) above.
- C. The City Manager is hereby authorized to adopt regulations as may be appropriate to implement, interpret and administer the provisions of this Section and to provide detailed Standards and Specifications, consistent herewith.
- D. All required improvements and landscaping shall be maintained in good repair and safe condition. Violation of this provision is hereby declared to be a nuisance which may be abated by the City in any lawful manner.
- E. Where there are practical difficulties or unnecessary hardships in the way of carrying out the strict letter of these requirements, upon written application, the City Council may vary or modify the application of these requirements, so that the spirit of the requirements is observed, public safety and welfare secured, and substantial justice done. (Ord. 6, §1, 2004; Ord. 4, §1 & 2, 2005)

PARKING DESIGN


6.50.01 Regular Parking

Conventional parking layout dimensions are provided in Table 6.50.01 and the detail drawithe Appendix of this Chapter. Other angled parking layouts meeting the approval of the Representative will be permitted where possible.

TABLE 6.50.01

Minimum Parking Layout Dimensions (In Feet) for 9-Foot Regular Parking Stalls at Various Angles

Dimension	On Diagram	<u>0</u>	<u>45</u>	Angle <u>60</u>	<u>75</u>	<u>90</u>
Stall Width, Parallel to Aisle	Α	9.0	12.7	10.4	9.3	9.0
Stall Length of Line	В	24.0	24.5	21.5	19.5	18.0
Stall Depth to Wall	С	9.0	17.0	18.5	19.0	18.0
Aisle Width Between Stall Lines	D	12.0	12.0	16.0	22.0	24.0
Stall Depth, Interlock	Е	9.0	14.8	17.0	18.3	18.0
Module, Wall to Interlo	ck F	30.0	43.8	51.5	59.3	60.0
Module, Interlocking	G	30.0	41.6	50.0	58.6	60.0
Module, Interlock to Curb Face	Н	30.0	41.8	49.4	56.9	58.0
Bumper Overhang (Typical)		0.0	1.5	1.8	2.0	2.0



6.50.02 Allowable Grades Permitted in Parking Lots

Minimum grades shall be the same as the grades set forth in Section 6.18.01. Maximum grades permitted in parking lots must not exceed eight percent (8%).

6.50.03 Handicapped Parking Requirements

Each handicapped parking stall shall be eight feet (8') in width with a five foot (5') unloading area, must have a stall depth of at least twenty four feet (24'), and be located near buildings and handicap ramps. The minimum required number of spaces is indicated in Table 8.12.02 below. A handicapped parking space will be required to be identified by an official "Handicapped Reserve Parking" (Manual on Uniform Traffic Control Devices, R7-8) sign with the handicapped person logo.

In order for handicapped parking spaces to function as intended, they will be required to be designed and signed in a uniform manner to allow for a clear understanding of the parking zone and to make enforcement possible. Signing of one, two, or three spaces for handicapped parking spaces must be done by using one sign for each space placed at the center of each end line.

Table 6.50.02

Minimum Required Number of Handicap Accessible Spaces

TOTAL PARKING SAPCES IN LOT OR GARAGE	MINIMUM REQUIRED NUMBER OF ACCESSIBLE SPACES
1-25	1
26-50	2
51-75	3
76-100	4
101-150	5
151-200	6
201-300	7
301-400	8
401-500	9
501-1,000	2% of total spaces
Over 1,000	20 spaces plus 1 space for every 100 spaces, or fraction thereof, over 1,000

6.50.04 Parking Structures

For design details and optimum layout of parking structures, reference to Parking Garage Planning and Operation, by the Eno Foundation for Transportation, Inc., Westport, 1978, or the Urban Land Institute Standards is recommended. The City will evaluate designs for such structures on an individual case basis.

17.04.230 Off-street parking requirements.

- A. The purpose of off-street parking requirements is to promote the convenient and safe movement of traffic on City streets.
- B. In those instances where there are clearly identified multiple uses within a structure or multiple structures, the minimum standards shall apply to each use or structure, resulting in a total parking requirement when summed.
 - C. Specific requirements are as follows:
- 1. Single, two, three and four family dwellings Two spaces per dwelling unit.
- 2. Multi-family dwellings with five or more units One and one-half spaces per dwelling unit plus one additional space per every five spaces.
 - 3. Theaters One space per each four seats.
 - 4. Bowling alleys Four spaces per lane.
- 5. Child care facilities One and one-half spaces per employee.
- 6. Adult care facilities One and one-half spaces per employee.
- 7. Churches One space per each three persons of capacity of the main sanctuary.
- 8. Assisted living facilities One-half space per apartment unit plus one for each three employees.
- 9. Hospitals One space for each three beds plus one for each three employees.
- 10. Funeral homes and mortuaries One space for each six seats in the main chapel.
 - 11. Nursing homes One space for each three beds.
- 12. Bed and breakfast operations Two spaces per dwelling unit plus one space per guest room.
 - 13. Hotels and motels One space per guest room.
- 14. Bus stations One space per four hundred square feet of floor area with a minimum of three spaces.
- 15. Offices, banks, medical-dental clinics, and government offices One space per three hundred square feet of gross floor area.
- 16. a. Restaurants One space per each three seats of seating capacity.
- b. Bars and nightclubs One space per each two persons designed capacity.
- 17. Drive-in restaurants One space per fifty square feet of floor area.
- 18. Beauty shops and barber shops Two spaces for each chair.
 - 19. Retail sales/service
- a. High volume retail sales (consists of supermarkets, clothing and department stores, shopping

complexes, hardware, building supplies, and similar uses) - One space per each two hundred square feet sales area.

- b. Low volume retail sales (consists of furniture/appliance sales, repair shops, nurseries, greenhouses and similar uses) One space per each two hundred fifty square feet sales area (includes employee parking).
- 20. Vehicles sales (such as automobile dealerships, used car sales, recreational vehicle sales, etc.) An area equal to ten percent of the total display area.
- 21. Car care establishments such as garages, oil and lube stops, tire sales and mounting Five spaces per 1,000 feet of gross floor area.
 - 22. Wholesale businesses 1.1 spaces per employee.
 - 23. Warehousing One space per employee.
 - 24. Industrial/manufacturing 1.1 spaces per employee.
- 25. Conditional use To be determined in conjunction with the conditional use review procedure.
- 26. For all uses not specified above, each premise shall provide adequate space to accommodate the anticipated need for parking generated by the use, including at least one space per employee.
- D. For all uses except single-family and two-family dwelling units, sufficient off-street space shall be provided to allow an automobile to enter, maneuver and exit without backing onto any public right-of-way, other than an alley.

E. Joint parking facilities

- 1. Off-street parking may be supplied by other off-street parking facilities for other uses if those other uses are not operated during the same hours, subject to the conditions of these specifications.
- 2. Off-street parking designated for joint use shall not be more than two hundred feet from the property or use it is intended to serve, except that employee parking may be farther if it is actually used by the employees.
- 3. Sufficient evidence shall be presented to demonstrate that there will be no substantial conflict in a joint parking arrangement.
- 4. Shared parking lots are allowed so long as the aggregate spaces required are provided and a recorded covenant or plat restriction on forms approved by the City allows the City to enforce compliance.
- F. When an area provides parking spaces for more than fifteen cars, at least five percent of the total area of the parking lot shall be landscaped in accordance with City specifications. A plan shall be submitted at the time of building permit application and shall be subject to City approval.

- G. When six or more spaces are required, the parking and maneuvering areas shall be paved in accordance with City specifications.
- H. Required off-street parking shall be contiguous to the use except as provided in Subsection (E), and except for residential users in the B-1 District which may utilize parking spaces owned or leased by the owner of the residential use if located within 450 feet of the residential use, or when a recorded covenant or plat restriction on forms approved by the City allows the City to enforce maintenance of the parking.
- I. Parking areas and required landscaping shall be designed pursuant to City Design Standards and Specifications.
- J. In the "B-1" District, or premises contiguous to the "B-1" District or directly across a street or alley from the "B-1" District, payment may be made to the City in lieu of providing required off-street parking spaces in the amount of \$2,700 per space. Such amount shall be kept and utilized by the City to provide public parking in said district.
- K. Off-street parking is not required for uses conducted within the "B-1" District except for residential and other specified uses which shall provide off-street parking at all locations. (Ord. 4, §1, 1999; Ord. 31, §2, 2000; Ord. 33, §1, 2002; Ord. 9, §18, 2004; Ord. 7, §14, 2005)